



BISHOP'S ORIGINAL PRODUCTS, Inc.

7111 CLINTON DR

HOUSTON, TX 77020

713/671-2545

FAX 713/671-0774

PRODUCT DATA SHEET

ANTI WEAR ALL PURPOSE PENETRATING LUBRICANT Formula 1773

Bishop's Original Anti Wear All Purpose Penetrating Lubricant is an exclusive formula engineered as an all purpose penetrating lubricant that exceeds today's rigid requirements for industrial use. The film forming barrier of protection provided by our exclusive penetrating lubricant reduces the need for frequent applications.

APPLICATION:

Home: Tools, Locks, Hinges, Fan Motors, Fishing Reels, Guns

Shop: Chains, Saw Blades, Air Tools, Latches

Industrial: Chain and Cables, Bearings, Bushings, Linkage

BENEFITS:

Prevents Formation of Rust
Reduces Friction and Wear
Frees Stuck Cables and Bolts
Helps Resist Abrasions
Penetrates Inaccessible Areas
Extreme Pressure Protection
Protects Against Moisture and Corrosion
Excellent Protection Against Salt Water Corrosion

SPECIFICATIONS:

Flash Point (COC)..... 395°F
Pour Point..... 21°F
API Gravity @ 60°F..... 24.1
Timken, OK Load..... 60 Lbs
Viscosity SUS @ 210°F..... 48.16
Viscosity Index..... 91
Falex E.P. Properties ASTM, D-3233 Equivalent True Load Failure. 4200 Lbs
Falex Wear Test ASTM, D-2670 Number of Teeth of Wear
15 minutes at 910 Ft-Lb true load..... 0
4 Ball Wear Test ASTM, D-4066, Average Scar Diameter MM..... 0.54
Salt Sea Spray, 100 hours in 5% NaCl Solution Fog..... No Rust

PACKAGING: 32 oz - 6 per case
64 oz - 6 per case
1 gallon - 4 per case

13 oz. Spray Can - 12 per case

This data is subject to variation, it is not to be used for specification purposes. Because we can not control conditions of use, we do not guarantee the results. Users of this product will make their own test to determine the suitability for their particular purpose. No statement we make about this product may be construed as a recommendation to infringe any patent.